

PFAFF 5626

Special longarm union feed chainstitch sewing machine (max. 12 needle)



Area of application:

Special operations in the areas leather, airbag, tire cord, e.g. straight sewing of transport belt fabric or tire cord fabric

Features:

- Very high stitch quality for top stitching and decorative seams
- High traction due to unison feed (bottom feed and alternating top and needle feed)
- The 5626 work with parallel located loopers which move in sewing direction (Inline)
- Simple threading, owing to swing-out loopers. All threading points are accessible from the front of the machine.
- High top feed stroke; max. 7 mm
- Fabric clearance under the foot: max. 14 mm
- Option: puller with automatic puller foot lift
- Option: integrated compressor
- Option: thread draw-off device for tension free and twist-free draw-off of the sewing threads
- Web pass height: on customer request
- Further fittings on request

Technical data:

- Max. sewing speed: 2,000 s.p.m.
- Stitch length (max.): 6,0 mm
- Needle gauges: 4,8 to 60 mm
- Arm clearance: 700 mm

PFAFF Industriesysteme und Maschinen GmbH

Hans-Geiger-Str. 12 – IG Nord
D-67661 Kaiserslautern

Telefon: +49-6301/3205-0

Telefax: +49-6301/3205-3171

E-mail: info@pfaff-industrial.com